Reflectix® Insulation

Technical Information

RSBW3

Single Bubble, Metalized One Side, White One Side

Reflectix® Insulation consists of one outer layer of metalized polyester and one layer of white polyethylene. Each layer is bonded to a tough layer of polyethylene for strength. One inner layer of insulating bubbles resist conductive heat flow.

Temperature Range:	**-30 degrees to +180 degrees F**
Nominal Thickness:	**3/16 inch (.188)**
Weight:	**.47 oz./sq. ft.**
Flame Spread Index (ASTM E 84):	**Less than 25**
Smoke Developed Index (ASTM E 84):	**Less than 50**
Fire Rating:	**Class A/Class 1**
Linear Shrinkage:	**None**
Reflectance (IR):	**96% (Metal Side)**
Fungi Resistance:	**No Growth**
Emittance:	**0.04 (Metal Side)**
Pliability:	**No Cracking / No Delamination**
Bleeding and Delamination:	**Passed**
Elevated Temperature & Humidity Resistance:	
Delamination:	**None**
Corrosion:	**None**
Loss of Metalization:	**None**
Permeance After Aging:	**0.01**
Permeance Before Aging:	**0.025**

Reflectix

#1 School St. (POB 108) Markleville, IN 46056 • (800) 879-3645
E: customerservice@reflectixinc.com • www.reflectixinc.com

T84 Rev 082026